



SM-CD

Versions of S.M Fluorescent Lamp

Outlook (General Data) SM-CD (3.0 ~ 120.0 μ F)

CAP	120-190vac		200-300vac		310-400vac		410-450vac		460-525vac	
μ F	D	L	D	L	D	L	D	L	D	L
3.0 μ F							30.0	52.0	30.0	52.0
3.5 μ F							30.0	52.0	30.0	52.0
4.0 μ F					30.0	52.0	30.0	52.0	35.5	52.5
4.5 μ F					30.0	52.0	30.0	52.0	35.5	52.5
5.0 μ F			30.0	52.0	30.0	52.0	30.0	52.0	35.5	52.5
5.5 μ F			30.0	52.0	30.0	52.0	35.5	52.5	35.5	52.5
6.0 μ F			30.0	52.0	30.0	52.0	35.5	52.5	35.5	52.5
6.5 μ F			30.0	52.0	30.0	52.0	35.5	52.5	35.5	52.5
7.0 μ F			30.0	52.0	35.5	52.5	35.5	52.5	40.5	60.5
7.5 μ F			30.0	52.0	35.5	52.5	35.5	52.5	40.5	60.5
8.0 μ F	30.0	52.0	30.0	52.0	35.5	52.5	35.5	52.5	40.5	60.5
9.0 μ F	30.0	52.0	30.0	52.0	35.5	52.5	40.5	60.5	40.5	60.5
10.0 μ F	30.0	52.0	35.5	52.5	35.5	52.5	40.5	60.5	40.5	65.0
12.0 μ F	30.0	52.0	35.5	52.5	40.5	60.5	40.5	60.5	40.5	65.0
14.0 μ F	30.0	52.0	35.5	52.5	40.5	60.5	40.5	65.0	45.5	77.0
15.0 μ F	30.0	52.0	35.5	52.5	40.5	60.5	40.5	65.0	45.5	77.0
16.0 μ F	35.5	52.5	35.5	52.5	40.5	60.5	40.5	65.0	45.5	77.0
18.0 μ F	35.5	52.5	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0
20.0 μ F	35.5	52.5	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0
22.0 μ F	35.5	52.5	40.5	60.5	40.5	65.0	45.5	77.0	52.0	90.0
23.0 μ F	35.5	52.5	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0
24.0 μ F	35.5	52.5	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0
25.0 μ F	35.5	52.5	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0
26.0 μ F	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0

Versions of S.M. **Fluorescent** capacitors - ISO-9001 certified

Dims. in mm. Temperature = 85°C
 Protected = 10,000 AFC

CAP	120-190vac		200-300vac		310-400vac		410-450vac		460-525vac	
μF	D	L	D	L	D	L	D	L	D	L
28.0 μF	40.5	60.5	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0
30.0 μF	40.5	60.5	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0
32.0 μF	40.5	60.5	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0
33.0 μF	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0	52.0	90.0
35.0 μF	40.5	60.5	45.5	77.0	45.5	77.0	52.0	90.0		
36.0 μF	40.5	65.0	45.5	77.0	45.5	77.0	52.0	90.0		
38.0 μF	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0		
40.0 μF	40.5	65.0	45.5	77.0	52.0	90.0	52.0	90.0		
42.0 μF	40.5	65.0	45.5	77.0	52.0	90.0				
44.0 μF	40.5	65.0	45.5	77.0	52.0	90.0				
45.0 μF	40.5	65.0	45.5	77.0	52.0	90.0				
47.0 μF	40.5	65.0	45.5	77.0	52.0	90.0				
50.0 μF	40.5	65.0	45.5	77.0	52.0	90.0				
55.0 μF	45.5	77.0	52.0	90.0	52.0	90.0				
60.0 μF	45.5	77.0	52.0	90.0	52.0	90.0				
65.0 μF	45.5	77.0	52.0	90.0						
70.0 μF	45.5	77.0	52.0	90.0						
75.0 μF	45.5	77.0	52.0	90.0						
80.0 μF	45.5	77.0	52.0	90.0						
85.0 μF	52.0	90.0								
90.0 μF	52.0	90.0								
95.0 μF	52.0	90.0								
100.0 μF	52.0	90.0								
120.0 μF	52.0	90.0								