



**BLOCK VARISTORS SERIES B32**  
**SPECIFICATION**

Model Number	Maximum Allowable Voltage		Varistor Voltage V1mA (V)	Clamping Voltage (Max.)		Maximum Peak Current (8/20μs)		Maximum Energy (JOULE) 10/1000 μS	Typical Capacitance (Reference) @1KHZ (pf)
	Acrms (V)	DC (V)		VC (V)	IP (A)	1 Time	2 Times		
			(A)						
B32K130	130	170	200(185-225)	340	200	25000	20000	210	5200
B32K150	150	200	240(216-264)	395	200	25000	20000	240	5100
B32K175	175	225	270(243-297)	455	200	25000	20000	255	4800
B32K210	210	275	330(297-363)	550	200	25000	20000	300	4300
B32K230	230	300	360(324-396)	595	200	25000	20000	315	3900
B32K250	250	320	390(351-429)	650	200	25000	20000	330	3200
B32K275	275	350	430(387-473)	710	200	25000	20000	360	3100
B32K300	300	385	470(423-517)	775	200	25000	20000	380	2800
B32K320	320	415	510(459-561)	845	200	25000	20000	430	2700
B32K385	385	505	620(558-682)	1025	200	25000	20000	470	2400
B32K420	420	560	680(612-748)	1120	200	25000	20000	495	2200
B32K460	460	615	750(675-825)	1240	200	25000	20000	520	2000
B32K485	485	640	780(702-858)	1290	200	25000	20000	550	1900
B32K510	510	670	820(738-902)	1355	200	25000	20000	580	1800
B32K550	550	745	910(819-1001)	1500	200	25000	20000	620	1300
B32K575	575	765	950(855-1045)	1570	200	25000	20000	650	1200
B32K625	625	825	1000(900-1100)	1650	200	25000	20000	685	1100
B32K680	680	895	1100(990-1210)	1815	200	25000	20000	750	1000
B32K750	750	970	1200(1062-1300)	2100	200	25000	20000	800	800
B32K880	880	1150	1400(1245-1520)	2290	200	25000	20000	850	680
B32K1000	1000	1200	1600(1414-1728)	2700	200	25000	20000	900	600

