



BLOCK VARISTORS SERIES B60
SPECIFICATION

Model Number	Maximum Allowable Voltage		Varistor Voltage V1mA (V)	Clamping Voltage (Max.)		Maximum Peak Current (8/20μs)		Maximum Energy (JOULE) 10/1000 μs	Typical Capacitance (Reference) @1KHZ (pf)
	Acrms (V)	DC (V)		VC (V)	IP (A)	1 Time	2 Times		
			(A)						
B60K130	130	170	200(185-225)	340	500	70000	50000	490	15000
B60K150	150	200	240(216-264)	395	500	70000	50000	570	12500
B60K175	175	225	270(243-297)	455	500	70000	50000	630	11000
B60K210	210	275	330(297-363)	550	500	70000	50000	680	9000
B60K230	230	300	360(324-396)	595	500	70000	50000	730	8500
B60K250	250	320	390(351-429)	650	500	70000	50000	880	7500
B60K275	275	350	430(387-473)	710	500	70000	50000	950	7000
B60K300	300	385	470(423-517)	775	500	70000	50000	1000	6500
B60K320	320	415	510(459-561)	845	500	70000	50000	1100	6000
B60K385	385	505	620(558-682)	1025	500	70000	50000	1300	5000
B60K420	420	560	680(612-748)	1120	500	70000	50000	1500	4500
B60K460	460	615	750(675-825)	1240	500	70000	50000	1600	4000
B60K485	485	640	780(702-858)	1290	500	70000	50000	1650	3900
B60K510	510	670	820(738-902)	1355	500	70000	50000	1800	3700
B60K550	550	745	910(819-1001)	1500	500	70000	50000	2000	3300
B60K575	575	765	950(855-1045)	1570	500	70000	50000	2100	3200
B60K625	625	825	1000(900-1100)	1650	500	70000	50000	2200	3000
B60K680	680	895	1100(990-1210)	1815	500	70000	50000	2500	2700
B60K750	750	970	1200(1062-1300)	2100	500	70000	50000	2600	2500
B60K880	880	1150	1400(1245-1520)	2290	500	70000	50000	3200	2400
B60K1000	1000	1200	1600(1414-1728)	2700	500	70000	50000	3300	2100
B60K1100	1100	1400	1800(1620-2060)	2940	500	70000	50000	3400	2000
V142BB60	1400	1750	2200(2020-2200)	3600	500	70000	50000	5500	1800
V172BB60	1700	2150	2700(2500-3030)	4300	500	70000	50000	6500	1500
V202BB60	2000	2500	3300(2970-3300)	5200	500	70000	50000	8000	1200
V242BB60	2400	3000	3900(3510-4290)	6200	500	70000	50000	9000	1000
V282BB60	2800	3500	4700(4230-5170)	7400	500	70000	50000	12000	800

