



## EPOXY COATING MOVS 60D SPECIFICATION

### 60D SPECIFICATION

Model Number 60mm	Maximum Allowable Voltage		Varistor Voltage	Clamping Voltage (Max.)		Maximum Peak Current (8/20 $\mu$ s)		Maximum Energy (JOULE)	Typical Capacitance (Reference)
	Acrms (V)	DC (V)	V1mA (V)	VC (V)	IP (A)	1 Time	2 Times	2ms	@1KHZ (pf)
						(A)			
60D201K	130	170	200(185-225)	340	500	80000	60000	490	15000
60D241K	150	200	240(216-264)	395	500	80000	60000	570	12000
60D271K	175	225	270(243-297)	455	500	80000	60000	630	10000
60D331K	210	275	330(297-363)	550	500	80000	60000	680	10000
60D361K	230	300	360(324-396)	595	500	80000	60000	730	9500
60D391K	250	320	390(351-429)	650	500	80000	60000	880	9000
60D431K	275	350	430(387-473)	710	500	80000	60000	950	8500
60D471K	300	385	470(423-517)	775	500	80000	60000	1000	7600
60D511K	320	415	510(459-561)	845	500	80000	60000	1100	7000
60D621K	385	505	620(558-682)	1025	500	80000	60000	1200	6600
60D681K	420	560	680(612-748)	1120	500	80000	60000	1500	6200
60D751K	460	615	750(675-825)	1240	500	80000	60000	1650	5800
60D781K	485	640	780(702-858)	1290	500	80000	60000	1700	5500
60D821K	510	670	820(738-902)	1355	500	80000	60000	1800	5000
60D911K	550	745	910(819-1001)	1500	500	80000	60000	1900	4500
60D951K	575	765	950(855-1045)	1570	500	80000	60000	2100	4200
60D102K	625	825	1000(900-1100)	1650	500	80000	60000	2200	4000
60D112K	680	895	1100(990-1210)	1815	500	80000	60000	2300	3800
60D122K	750	970	1200(1062-1300)	2100	500	80000	60000	2600	3500
60D142K	880	1150	1400(1245-1520)	2290	500	80000	60000	3200	3000
60D162K	1000	1200	1600(1414-1728)	2700	500	80000	60000	3200	2500
60D182K	1100	1400	1800(1620-2060)	3030	500	80000	60000	3200	2200
60D222K	1400	1750	2200(2020-2200)	3580	500	80000	60000	5000	1800
60D272K	1700	2150	2700(2500-3030)	4400	500	80000	60000	6000	1500
60D332K	2000	2500	3300(2970-3300)	5375	500	80000	60000	7500	1200

**Electronic Alliance**

[www.eaa.net.au](http://www.eaa.net.au)

60D392K	2400	3000	3900(3510-4290)	6360	500	80000	60000	8600	1000
60D472K	2800	3500	4700(4230-5170)	7665	500	80000	6000	10000	800

