



TMOV WITH INBUILT THERMAL CUTOFF T34S SPECIFICATION

Model Number 34mm	Maximum Allowable Voltage		Varistor Voltage V1mA (V)	Clamping Voltage (Max.)		Maximum Peak Current (8/20μS)		Maximum Energy (JOULE) 10/1000 μS	Typical Capacitance (Reference) @1KHZ (pf)
	Acrms (V)	DC (V)		VC (V)	IP (A)	1Time	2Times		
			(A)						
T34S201KM	130	170	200(185-225)	340	300	40000	30000	310	6800
T34S221KM	140	180	220(198-242)	360	300	40000	30000	330	6200
T34S241KM	150	200	240(216-264)	395	300	40000	30000	360	5700
T34S271KM	175	225	270(243-297)	455	300	40000	30000	390	5000
T34S331KM	210	275	330(297-363)	550	300	40000	30000	410	4100
T34S361KM	230	300	360(324-396)	595	300	40000	30000	460	3800
T34S391KM	250	320	390(351-429)	650	300	40000	30000	490	3500
T34S431KM	275	350	430(387-473)	710	300	40000	30000	550	3200
T34S471KM	300	385	470(423-517)	775	300	40000	30000	600	2900
T34S511KM	320	415	510(459-561)	845	300	40000	30000	640	2700
T34S561KM	350	460	560(504-616)	920	300	40000	30000	710	2400
T34S621KM	385	505	620(558-682)	1025	300	40000	30000	800	2200
T34S681KM	420	560	680(612-748)	1120	300	40000	30000	910	2000
T34S751KM	460	615	750(675-825)	1240	300	40000	30000	980	1800
T34S781KM	485	640	780(702-858)	1290	300	40000	30000	1020	1750
T34S821KM	510	670	820(738-902)	1355	300	40000	30000	1100	1650
T34S911KM	550	745	910(819-1001)	1500	300	40000	30000	1150	1500
T34S951KM	575	765	950(855-1045)	1570	300	40000	30000	1200	1430
T34S102KM	625	825	1000(900-1100)	1650	300	40000	30000	1250	1360
T34S112KM	680	895	1100(990-1210)	1815	300	40000	30000	1350	1250
T34S122KM	750	970	1200(1062-1300)	2000	300	40000	30000	1400	1200
T34S142KM	880	1150	1400(1245-1520)	2290	300	40000	30000	1450	1100
T34S162KM	1000	1200	1600(1414-1728)	2550	300	40000	30000	1500	1000

