

70W Universal Input



70W Universal Input

Product feature:

- Battery reverse charge protection
- Protection for deeply discharged battery
- Overload/ Short circuit Protection
- Approvals:CE

AC input / full range

Power on indication

Cooled by air convection

Metal case, small size

100% full load burn-in test

1 year warranty

Size:160mm×98mm×42mm

Specifications:						
AC input voltage:	100VAC~240 VAC					
Input frequency:	47~63Hz					
Inrush Current:	40A@ 220VAC					
Hold up time:	20 ms at 120VAC					
Overload protection	105%-180% of the rated maximum output power					
Working temperature:	0 to 40°C					
Safety standard:	GB4943-2001					
	EN60950					
EMC standard:	EN55022					
Withstand Voltage:	I/P-OP: 3KVAC/min					
	I/P-FG: 1.5KVAC/min					
	O/P-FG: 0.5KVAC/min					
Connection	I/P:JTB552-00-1-05-3-M9					
	O/P:JTB552-00-1-02-3-M9					
MTBF:	>100000h					
Weight:	0.65Kg/pcs					
P/N	DC Output	Tol.	R&N	Effi.	Load Regulation	Line Regulation
ESP-70-13.8A	13.8VDC 0~5A	±2%	140mV	80%	±2%	±1%
ESP-70-27.6A	27.6VDC 0~2.5A	±2%	240mV	80%	±2%	±1%