



**Electronic Alliance**

## 75W Single Output (Din-rail)



### 75W Single Output (Din-rail)

Product feature :

Universal AC input/ full range

Power on indication

Cooling by air convection

Overload /Over voltage /Over temperature/Short Circuit Protection

100% full load burn-in test

Installed on Din rail TS35/7.5 or 15

1year warranty

Size:55.5mm x 125.2mm x 100mm

<b>Specifications:</b>	
AC input voltage:	88~264VAC 120-370VDC
Input frequency:	50Hz
Inrush current:	60A@230VAC
	30A@115VAC
Overload protection:	full load, cold start
	105%- 150%
	constant current limiting
Over voltage protection:	auto-recovery
	121%-142 %
Setup, rise,hold up time:	rated output voltage
	1000ms,60ms,50ms
Working temperature:	at full load and 230VAC
	-10 to 60°C
Safety standard:	refer to output derating curve
EMC standard:	UL508
MTBF	EN55022 class B EN61000-3-2,3 EN61000-6-2
	EN61000-4-2,3,4,5,6,8,11
Connection:	100000 h at 25°C
Weight	I/P:3 poles
	O/P: 4 poles screw DIN terminal

P/N	Output	Tol.	R&N	Effi.	DC adjustment range
DP-75-12	12V,0~6.3A	±2%	100 mV	84%	12~14V
DP-75-24	24V,0~3.2A	±1%	150 mV	88%	24~28V
DP-75-48	48V,0~1.6A	±1%	240 mV	88%	48~53V