



30W Double Output



30W Double Output

- Universal AC input/ full range
- air cooling
- Overload / Short Circuit Protection
- 100% full load burn-in test
- One year warranty
- Available for cashier machine

Specifications

AC input voltage	176~264VAC					
Input frequency	47~53Hz					
Inrush current	40A @230VAC full-load, cold start					
hold up time	16 ms @230VAC					
Working temperature	0 to 50°C					
Safety standard	UL60950					
EMC standard	EN55022 class B					
MTBF	10 ⁵ h at 25°C					
Withstand Voltage	I/P-O/P:1.5KV I/P-FG:1.5KV,1min/5mA					
Weight	0.2Kg/pcs					
P/N	Output	Tol.	R&N	Effi.	Load Regulation	Line Regulation
EPD-30A	24V,0~1A	±1%	50mV	70%	±1%	±1%
	5V,0~1A	±2%	50mV	70%	±2%	±2%
EPD-30B	24V,0~1A	±1%	50mV	70%	±1%	±1%
	7.5V,0~1A	±2%	50mV	70%	±2%	±2%
EPD-30C	48V,0~0.6A	±1%	200mV	70%	±1%	±1%
	5V,0~1A	±2%	50mV	70%	±2%	±2%
EPD-30D	12V,0~2A	±2%	50mV	70%	±1%	±1%
	5V,0~1A	±2%	50mV	70%	±2%	±2%