



40W Triple Output



40W Triple Output

- Universal AC input/ Full range
- Power on indication
- Cooling by free air convection
- Short circuit / Over load Protection
- 100% full load burn-in test
- One year warranty
- 130×98×40mm

Specifications

AC input voltage	90~264VAC 127~370VDC					
Input frequency	47~63Hz					
Inrush current	50A @230VAC full load cold start 30A @115VAC full load cold start					
Set-up time	500ms					
hold up time	20ms@ full load,230VAC					
Over voltage protection	≥150% 110~135%					
Working temperature	0 to 40°C					
Safety standard	UL60950-1,TUV EN60950-1					
EMC standard	EN55022 class B, EN61000-3-2,3 EN61000-4-2,3,4,5,6,8,11					
MTBF	10 ⁵ h at 25°C					
Withstand Voltage	I/P-O/P:2KVAC I/P-FG:1.5KVA, 1min					
Connection	9P/9.5mm 端子排					
Weight	0.6Kg/pcs					
P/N	Output	Tol.	R&N	Effi.	Load Regulation	Line Regulation
EPT-40A	5V,0.5~4A	±2%	100mV	70%	±2%	±1%
	12V,0~1A	±2%	150mV		±2%	±1%
	-12V,0~0.5A	±5%	150mv		±5%	±3%