



Electronic Alliance

35W Single Output



35W Single Output

Universal AC input/ full range
 Overload /Short Circuit Protection
 100% full load burn-in test
 One year warranty
 129mm*98mm*38mm

Specifications						
AC input voltage	85~264VAC					
Input frequency	47~63Hz					
Input current	1A /0.5A 115VAC/115VAC					
Inrush current	36A @ 230VAC 18A @ 115VAC					
hold up time	30ms at 230VAC					
Working temperature	-10 ~ 60°C					
Safety standard	UL1950 EN60950 CSA 22.2 No CE Mark					
EMC standard	EN61000-4-2 EN 61000-4-6 EN61000-4-3 EN61000-4-8 EN61000-4-4 EN61000-4-9 EN61000-4-5 EN61000-4-11					
MTBF	10 ⁵ h at 25°C					
Withstand Voltage	I/P-O/P:3KV I/P-FG:1.5KV,1min/5mA					
Weight	0.41Kg/pcs					
P/N	Output	Tol.	R&N	Effi.	Load Regulation	Line Regulation
ESP-35-5	5V,0~7A	±2%	75mV	78%	±2%	±1%
ESP-35-12	12V,0~3A	±1%	100mV	80%	±1%	±1%
ESP-35-15	15V,0~24A	±1%	100mV	84%	±1%	±1%
ESP-35-24	24V,0~1.5A	±1%	100mV	85%	±1%	±1%