



## 400W Single Output



### 400W Single Output

High reliability  
 Universal Ac input/full range  
 100% full load burn-in test  
 Protections: overload/short circuit/over current protection  
 One year Warranty  
 Cooled by air convection  
 Size:227mmx 100mmx 69mm

<b>Specifications:</b>				
AC input voltage range:		90~132V AC		170~264V AC
Input frequency:		47~63HZ		
Output adjustment range:		±5%~±10%		
Output over load protection:		110~150%		
Withstand voltage:		I/P-O/P:3KV AC, 1min		
		I/P-F/G:1.5KV AC, 1min		
Rise time:		50ms		
Hold up time:		20ms		
Working temperature:		-10~+50°C		
Storage temperature:		-20°C~+85°C		
Safely and EMC standards:		GB4943		
		UL60950		
		EN60950		
		GB9254		
		EN55022 A		
MTBF:		>50000h		
Weight:		1.25Kg		
P/N	Output	Load regulation	R&N	Effi.
ESP-400-9	9V 44A	2.0%	120mV	82%
ESP-400-12	12V 33A	2.0%	120mV	83%
ESP-400-15	15V 26A	2.0%	150mV	83%
ESP-400-24	24V 16.6A	2.0%	150mV	83%
ESP-400-27	27V 14.8	2.0%	160mV	84%
ESP-400-36	36V 11A	2.0%	180mV	85%
ESP-400-48	48V 8.3A	2.0%	200mV	86%