



**Electronic Alliance**

## 25W Single Output (Mini-size)



### 25W Single Output (Mini-size)

Universal AC input/ full range  
 Power on indication  
 Overload /Over voltage /Short Circuit Protection  
 100% full load burn-in test  
 One year warranty

Size:79mm x 51mm x 28mm

### Specifications:

AC input voltage	88~264VAC, Nominal 100-240VAC					
Input frequency	47~63Hz					
Inrush current	40A @230VAC,full load cold start					
hold up time	80ms@230 VAC,100% of rated maximum load					
Overload protection	110%- 150%					
Over voltage protection	110%-140%					
Working temperature	-10 to 50°C					
Safety standard	UL60950-1					
EMC standard	EN55022 class B					
MTBF	10 <sup>5</sup> h at 25°C					
Withstand Voltage	I/P-O/P:3KV,I/P-FG:1.5KV,1min					
Weight	0.2Kg/pcs					
<b>P/N</b>	<b>Output</b>	<b>Tol.</b>	<b>R&amp;N</b>	<b>Effi.</b>	<b>LoadRegulation</b>	<b>Line Regulation</b>
<b>ESPR-25-3.3</b>	<b>3.3V,6A</b>	3%	80mV	72%	3%	3%
<b>ESPR-25-5</b>	<b>5V,5A</b>	2%	80mV	77%	2%	2%
<b>ESPR-25-12</b>	12V,2A	1%	120mV	79%	1%	1%
<b>ESPR-25-24</b>	24V,1.1A	1%	120mV	84%	1%	1%
<b>ESPR-25-48</b>	48V,0.57A	1%	200mV	85%	1%	1%