



FOR 4 CCFL



FOR 4 CCFL

- Full bridge phase shift drive , zero voltage switching
- Balanced lamp current
- Open lamp protection
- High efficiency

Temperature:
 Storage: -25~70°C
 Operation: 0~70°C

Humidity:
 Storage: 10%~95%RH, non-condensing
 Operation: 10%~95%RH, non-condensing

MTBF: 60,000Hrs@25°C

Specifications		
Applied for LCD	15'/17'/19'	For 4 CCFL
Dimension(mm)	156X45.5X10	
Input Voltage(V)	10.8~13.2	
Typical input voltage(V)	12	
Input Current(A) type	1.8	Vin=12V, Von/off=5V, Vadj=0V
Lamp current(mA) Type	6.6	Vin=12V, Von/off=5V, Vadj=0V
	3.0	Vin=12V, Von/off=5V, Vadj=5V
Frequency(KHZ)	40~55	Vin=12V, Von/off=5V, Vadj=0V

Pin Assignments

1.DC Input: Location: CN1,CN6

CN1:

Pin NO.	Symbol	Description
1	Vin	12V
2,4	GND	Power Return
3	Vadj	Brightness
5	Von/off	On/Off Control



FOR 4 CCFL

CN6:

Pin NO.	Symbol	Description
10,11,12	Vin	12V
1,3,5,6,8,9	GND	Power Return
2	Vadj	Brightness
4	Von/off	On/Off Control
7	NC	NC

2.AC

Output: Location: CN2,CN3,CN4,CN5

Pin NO.	Symbol	Description
1	HV	High Voltage
2	LV	RETURN