



Electronic Alliance

60W Single Output (Open Frame)



60W Single Output (Open Frame)

Universal AC input/ Full range
 Power on indication
 Cooling by free air convection
 Short circuit /Over voltage/Over load Protection
 100% full load burn-in test
 One year warranty
 127×76.2×26.5mm

Specifications				
AC input voltage		90~264VAC		
Input frequency		47~63Hz		
Inrush current		40A @230VAC full load, cold start		
		25A @115VAC full load, cold start		
Set up time		1sec @ 230VAC		
Hold up time		20ms@full load,230VAC		
Over voltage protection		110%- 135%		
Working temperature		0 to 50°C		
Safety standard		IEC60950 IEC60065		
EMC standard	EN61000-3-2	EN55022 (1998) + A1 + A2		
	EN61000-3-3 + A1	EN55013 (2001)+A1		
	EN61000-4-5	EN55020 (2002) + A1		
	EN61000-4-4	EN55024(1998)		
	EN61000-4-11	EN61000-4-2+A1 + A2		
MTBF		10X105 h at 25°C		
Withstand Voltage		I/P-O/P:3KVAC1 min/6mA		
Connection		3P/6P 3.96mm ; HX39603-3A HX39603-6A		
Weight		0.3Kg/pcs		
P/N	Output	R&N	Effi.	Line Regulation
OP-60-5	5V,0~12A	50mv	76%	±1%
OP-60-12	12V,0~5A	100mv	80%	±1%
OP-60-24	24V,0~2.5A	240mV	83%	±1%