



Electronic Alliance

150W Single Output (U-Bracket)



150W Single Output (U-bracket)

AC input range selectable by switch
 auto-sensing
 Overload /Short Circuit Protection
 100% full load burn-in test
 One year warranty
 7" X 5" X 2"

Specifications						
AC input voltage		88~132VAC/176~264VAC				
Input frequency		47~63Hz				
Inrush current		35A @110VAC 全载冷态				
hold up time		20ms				
Over voltage protection		110%-140%				
Working temperature		0 ~ 50°C				
Safety standard		UL60950-1				
EMC standard		EN55022 class B				
MTBF		10 ⁵ h at 25°C				
Withstand Voltage		I/P-O/P:3KV I/P-FG:1.5KV,1min/5mA				
Weight		1Kg/pcs				
P/N	Output	Tol.	R&N	Effi.	Load Regulation	Line Regulation
UP-150-12	12V,0-12.5A	+/-1%	120mV	75%	+/-1%	+/-1%
UP-150-15	15V,0-10A	+/-1%	150mV	75%	+/-1%	+/-1%
UP-150-24	24V,0-6.3A	+/-1%	200mV	77%	+/-1%	+/-1%
UP-150-48	48V,0-3.2A	+/-1%	200mV	79%	+/-1%	+/-1%