



Electronic Alliance

180W Single Output (U-Bracket)



180W Single Output (U-bracket)

Product feature :

- Universal AC input/Full range
- PF>0.97@115Vac,>0.93@230Vac
- Protections: Short circuit/Overload/Over voltage
- Free air convection for 150W and 180W with 18CFM forced air from outside of the power supply
- 100% full load burn-in test
- 202*103*38mm
- 1 year warranty

Specifications:	
AC input voltage:	90~264VAC
Input frequency:	47~63Hz
Inrush current:	30A @115VAC 60A @ 230VAC cold start
set up time:	1second@ 230VAC
hold up time:	20ms@120VAC and 80% of rated maximum load
Over voltage protection:	110~135%
Over load protection:	105~150%
Working temperature:	0 to 50°C
Safety standard:	UL1950, EN60950
EMC standard:	EN55022 class B, EN61000-3-2,3 EN61000-4-2,3,4,5,6,8,11 ENV50204
MTBF:	10 ⁵ h at 25°C
Withstand Voltage:	I/P-O/P:3KVAC,1min/5mA I/P-FG:1.5KVAC,1min/5mA
Connection:	3P/5P 3.96mm HX39601-3A HX39603-8A
Weight:	0.85Kg/pcs



Electronic Alliance

180W Single Output (U-Bracket)

P/N 型号	DC Output 输出	Tol. 容差	R&N 纹波&噪声	Effi. 效率	Load Regulation 负载调整率	Line Regulation 线性调整率
UP-180-5	5V,0.1~30A	±2%	100mV	75%	±2%	±1%
UP-180-12	12V,0.1~15A	±2%	100mV	75%	±2%	±1%
UP-180-24	24V,0.1~7.5A	±2%	150mV	77%	±2%	±1%
UP-180-48	48V0.1~3.8A	±2%	250mv	79%	±2%	±1%