



Electronic Alliance

120W Triple Output (U-Bracket)



120W Triple Output (U-bracket)

Universal AC input/ Full range
 100% full load burn-in test
 One year warranty
 178mm x 102mm x 51mm

| Specifications | | | | | | |
|---------------------|-------------------|--|-------|-------|-----------------|-----------------|
| AC input voltage | | 90~264VAC Nominal 100~240VAC | | | | |
| Input frequency | | 47~63Hz | | | | |
| Inrush current | | 50A @230VAC full load cold start 35A @110VAC full load cold start | | | | |
| hold up time | | 20ms | | | | |
| Working temperature | | 0 to 40°C | | | | |
| Safety standard | | UL1950 CSA60950 | | | | |
| EMC standard | | Class B (FCC, CISPR 22) | | | | |
| MTBF | | 10 ⁵ h at 25°C | | | | |
| Withstand Voltage | | I/P-O/P:3KV I/P-FG:1.5KV,1min/5mA | | | | |
| Weight | | 0.9Kg/pcs | | | | |
| P/N | Output | Tol. | R&N | Effi. | Load Regulation | Line Regulation |
| UPT-120A | +5VDC 0.8A-8A | +/-1% | 150mV | 70% | +/-1% | +/-1% |
| | +12VD 0.6A-6A | +/-1% | 200mV | | +/-1% | +/-1% |
| | -12VDC 0.08A-0.8A | +/-5% | 250mV | | +/-5% | +/-5% |